



Ideal filtration for multi-use applications

Benefits

- Reduces chloramine and chlorine taste and odor effects as well as other offensive contaminants.
- Antimicrobial protection inhibits potential bacterial growth.
- Submicron filtration reduces dirt and particles as small as 1 micron in size and possible health contaminants such as cryptosporidium and giardia cysts.
- Protects drink system equipment from clogging, corrosion and abrasive wear.

Specifications

- **Rated Capacity at 1.7 GPM (6.4 LPM):**
Chloramine 3,600 Gallons (13,627 Liters)
Chlorine 9,000 Gallons (34,069 Liters)
- **Pressure Requirements:**
10 – 125 psi (0.7 – 8.6 bar), non-shock
- **Temperature:**
35 - 100°F (2 - 38°C)

No electrical connection required

Operating Recommendations

- Please read and understand entire manual before attempting to assemble, operate and install the filtration system. Installation must comply with state and local laws.
- Risk of leaks, which could lead to flooding, if not installed according to the instructions.
- Proper maintenance of the filtration cartridges is one of the most critical steps to ensuring quality water and equipment longevity.
- The cartridge capacity is dependent upon usage and overall quality of supply water. Cartridges typically last six months; however, when pressure on the exit gauge drops below 10 psi, that is an indicator that the cartridges are clogged and should be replaced.
- Upon installation of the new cartridges, it is recommended that you label them with the install date for tracking purposes.

The contaminants or other substances removed or reduced by this water filtration system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.