

Features

- 1.4L / .37G stainless steel hot tank
- 3.55L /.94G stainless steel cold tank
- Larger 10" dispensing area to accommodate a variety of container sizes
- Lighted spout and dispensing area
- Safety lock for hot & cold water
- Features fast flow water dispensing
- Removable, dishwasher safe drip tray
- Available in black and white
- UL Listed

- Accu-Temp® Serves water at the proper temperature every time
- **Highly Energy Efficient** Consumes less than one kW-h/day in normal operating mode, and even less in Energy Saving mode
- **iBoil** Increases the hot water temperature to just under boiling—perfect for barista quality coffee, teas, and cooking noodles and soups
- **SIP® enhanced** Programmable sanitization. Sanitizes cold reservoir, waterways and spout (optional)
- Stay-Cool® Keeps residual water in the cold waterway chilled and ready to serve



Horizons® CT Filtration Cooler

Δ



Power

Voltage	115, 2
Frequency (Hz)	50/60
Power Consumption	4.83A
Cold Power Consumption	1.51A
Hot Power Consumption	3.87A
ES (kWh/24 hrs.)	.755
% lower than ES Standard	13%

115, 220, 100 50/60 4.83A / 547W / 115V 1.51A / 109.4W / 115V 3.87A / 449W / 115V .755 13%

Hot Water System

Avg. Hot Water Temp at Nozzle @75°F Ambient (Before/After On)	176°F / 190°F
Hot Water ARI Rating	37, 6oz > 165°F +/- 10%
Hot Thermometer / Heat Limiter	203°F
Hot Thermostat / Thermister Cycle	140°F – 198°F
Hot Water Flow Rate	1.240 - 01.46 oz/sec
Hot Tank Size (Liter : Gallon)	1.4L : .37G
Heat Band Wattage	450W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F ambient (Before/After ON)	42°F / 48°F
Cold Water ARI Rating	24, 5oz < 50°F +/- 10%
Cold Thermostat Set Point	45°F + 3°/-8°F
Cold Water Flow Rate	1.24 – 01.46 oz/sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gallon)	3.55 / 2.64 / 1.32 : 0.94 / 0.7 / 0.35

Weights and Measurements

Net Weight (Lbs)	35.3
Gross Weight (Lbs)	38.4
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.8x17.1x17.5 / 13.4x17.7x18.5
Container Load (20')	340
Container Load (40')	700
Container Load (40' HC)	875
Container Load (45" HC)	979
Certifications	UL Listed

